



**TECHNICAL SPECIFICATIONS**

**SUPERIOR CHOPPED STRAND**

**C352**

**PRODUCT CODE 5140064  
 ECS 407 – 12MM**

**Product Description**

Superior Chopped Strand, C352, is a high performance E-glass chopped strand and is designed for compression, injection and transfer molding processes. It is compatible with polyester and vinyl ester resin system.

**Product Characteristics**

- Excellent dry flow characteristics.
- Good strand integrity, low static and low fuzz.
- Fast wetting.
- Excellent mechanical properties.
- Silane coupling agent.

**Technical Specifications**

Type of fiberglass	E glass
Filament diameter (um)	13+/- 1
LOI (%)	1.5+/- 0.15
Moisture (%)	Max. 0.1
Fiber length (mm)	12+/-1
Fiber length (inch)	½"

**400 WEST REGENT / INDIANAPOLIS, INDIANA 46225 / TELEPHONE (317)718 – 4400**  
 St. Louis, MO      Springfield, MO      Cincinnati, OH      Louisville, KY      Elkhart, IN      Effingham, IL  
 (314) 621 -2600      (417) 862-6245      (513) 870-9271      (502) 449-1184      (219) 264-0161      (217) 342-4390

This informatino is based on data available to us and is accurate and reliable to the best of our knowledge at the time of printing. However, no warranty is expressed or implied regarding the accuracy or completeness of the information contained herein. Final determination of the suitability of this material for the use contemplated is the sole responsibility of the user. Buyer assumes all risk and liabilities. Buyer accepts and uses this material on these conditions.