

MATERIAL SAFETY DATA SHEET CEMENT MODIFIER



MANUFACTURED BY:

InCide Technologies, Inc. (Complete Coatings) EMERGENCY CONTACT: (602) 233-0756

50 North 41st Ave. Phoenix, AZ

DATE OF PREP: 1/20/07 REVISED: 8/5/09

SECTION I PRODUCT IDENTIFICATION

PRODUCT CODE: P.SURECUREPLUS PRODUCT NAME: SureCure Plus

STYRENE-ACRYLIC COPOLYMER SEALER

SECTION II HAZARDOUS INGREDIENTS

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM

HEALTH: 1 FLAMMABILITY: 1

REACTIVITY: 0

INGREDIENT CAS# % BY WEIGHT OSHA HAZARD DOT HAZARD

STYRENE-ACRYLIC COPOLYMER PROPRIETARY 43% Y N DIPROPYLENE GLYCOL MONOBUTYL ETHER 29911-28-2 1-3% Y N DIBUTYL PHTHALATE 84-74-2 <1% Y Y

SECTION III PHYSICAL DATA

BOILING RANGE: >100C PERCENT VOLATILE BY VOL: 32-34
SPECIFIC GRAVITY: 1.04 EVAPORATION RATE: unknown
VAPOR DENSITY: (Air = 1) not established VOLATILE ORGANIC CONTENT: 481 grams/liter
APPEARANCE AND ODOR: translucent liquid – sweet odor pH: 8.0-9.3

SOLUBILITY IN WATER: complete

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA

SECTION IV FIRE AND EXPLOSION DATA

FLASH POINT: >200 Deg F

GENERAL HAZARDS: CO2, CO, ammonia and nitrogen oxides may be evolved Use NIOSH/MSHA self-contained breathing apparatus.

EXTINGUISHING MEDIA: CO2, dry powder, chemical foam

FIRE FIGHTING EQUIPMENT: Self-contained breathing apparatus and full protective clothing

HAZARDOUS COMBUSTION PRODUCTS: CO2, CO, dense smoke, irritating vapors

AUTO IGNITION TEMPERATURE: Not established LEL AND UEL: Not established

SECTION V HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Appearance: Translucent Liquid ODOR: Sweet Odor

This product is an EYE IRRITANT. Keep away from open flame, ignition sources and electricity. Use only in properly ventilated area.

SECTION V HAZARDS IDENTIFICATION

Potential Health Effects:

Routes of Entry: Ingestion

Eye: Product is an eye irritant

Skin: Not a skin irritant. May cause drying of skin when in contact for long periods of time.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea; kidney, ureter,

and

bladder changes.

Inhalation: Excessive inhalation of vapors may cause nasal and respiratory irritation.

Target Organ Effects: Eye irritant.

Medical Conditions Aggravated: Unknown. May aggravate respiratory, eye, and dermal conditions

Effects of Overexposure: Read this entire section

SECTION VI FIRST AID MEASURES

Eyes: Flush eyes for at least 15 minutes while holding eyelids apart. Seek medical attention if irritation develops.

Skin: Remove contaminated clothing and wash exposed area with soap and water.

Ingestion: Keep person warm and quiet and get medical attention. Induce vomiting as directed by medical personnel.

Inhalation: Remove person to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, administer

artificial respiration, and get medical attention.

SECTION VII ACCIDENTAL RELEASE (SPILL) MEASURES

Highway or Rail Spill: Call CHEMTREC: 1-800-424-9300

Large Spill Procedure: Eliminate all ignition sources. Rescue persons in danger. Remove all persons not wearing

protective equipment from the area. Secure the spill site. Contain the spill by diking to prevent runoff into water areas. Recover spilled material and specify container for reuse,

recycling or disposal.

Small Spill Procedure: Eliminate all ignition sources. Recover spilled material and specify container for reuse,

recycling or disposal.

SECTION VIII HANDLING AND STORAGE

Handling: Use appropriate personal protective equipment.

Keep away from ignition sources. Use in appropriately ventilated areas.

Storage: Store in cool ventilated areas, away from ignition sources.

Do not allow product to freeze.

SECTION IX EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:

Eye Protection:

Safety glasses with side shields or goggles.

Skin Protection:

Gloves and appropriate outer clothing.

Respiratory Protection: NIOSH approved ventilator.

Other Protective Equipment: Lab coat or coveralls. See supervisor for appropriate PPE.

Exposure Guidelines (Nuisance Particulates): ACGIH: TWA=10 mg/m3

For dibutyl phthalate, AGIH:TWA 5mg/m3; OSHA: PEL 5 mg/m3

SECTION X STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions To Avoid: High temperatures over 70 Deg C or freezing temperatures, and open flame.

Hazardous Decomposition Products: CO2, CO, dense smoke, irritating vapors.

Hazardous polymerization: Stable

SECTION XI TOXICOLOGICAL INFORMATION

LD50 (oral-rat): For dibutyl phthalate: 8000 mg/kg

LDLO (oral-human):

LC50 (inhalation rats):

Sub chronic effects:

Not Established

Not Established

Reproduction Information: Reproductive effects for dibutyl phthalate have been reported.
Teratology (Birth Defect): Teratogenic effects for dibutyl phthalate have been reported:
Mutagenicity (Genetic Effects): Mutation data for dibutyl phthalate has been reported.

SECTION XII ECOLOGICAL INFORMATION

Ecotoxicological Information: Not Established Chemical Fate Information: Not Established

SECTION XIII DISPOSAL CONSIDERATIONS

For disposal purposes, this product is not considered a hazardous waste, and should be treated accordingly. Incineration is suggested, but local, state, and federal regulations must be followed. Off site disposal should be made using a reputable waste disposal company.

SECTION XIV TRANSPORT INFORMATION

Non-Bulk packagings transported by highway, rail, or air are not regulated by the DOT. Request specific guidance for bulk shipments or shipments by vessel (water).

DOT (Department of Transportation)

Proper Shipping Name:
Hazard Class:
Identification Number:
Packing Group:
Label:
Not Regulated
Not Required
Not Required
Not Required
Not Required

SECTION XIV TRANSPORT INFORMATION

ICAO (International Civil Aviation Organization)

Proper Shipping Name:
Hazard Class:
Identification Number:
Packing Group:
Label:
Not Regulated
Not Required
Not Required
Not Required
Not Required

SECTION XV REGULATORY INFORMATION

Federal Regulations:

United States:

OSHA (29 CFR 1910.1200): See Section II and VIII for details.

CERLA (40 CFR 302.4): Reportable Quantity for Dibutyl phthalate: 5 pounds (500 pound product)

RCRA: Listed waste (dibutyl phthalate): UO69/FO39

California Proposition 65: The required chemical analyses and risk assessments were performed on

this

product. Results indicate that there are no significant risks (or observable effects), as defined by this statute, associated with this product under

conditions of normal use.

SARA Section 313: Dibutyl phthalate is above the de minimis level.

Hazard Category: Acute: (Irritant: Eye)
State Right to Know Acts (MA, NJ, PA): NJTSR#: PFX-2959-07

Canada:

WHMIS: Dibutyl Phthalate is listed on the Ingredient Disclosure List.

NPRI: Dibutyl Phthalate is on the Canadian NPRI.

Regulatory Listings:

United States (TSCA): Listed on the TSCA Chemical Inventory

Canada (CEPA): Not Determined

Europe (EINECS): This product is either listed, or considered an EC polymer.

Australia (AICS):

Japan (MITI):

Not Listed

Not Listed